



SPECIFICATIONS

MADE FROM : 7026
QUOTE : 17-65-049
CUSTOMER : BCTE
JOB : TBD
DELIVERY : SEPTEMBER 2017

17 SHELL SUBFRAME STAINLESS STEEL CROSSMEMBERS AND OUTRIGGERS, 3/16" SILLS, FRAME LESS

18 INSULATION N/A

19 OUTER SHELL N/A

REAR CABINET

20 TYPE OF CABINET N/A

21 PIPING 316L 3" SCH40

22 VALVE(S) 1 4"X3" EMERGENCY EXTERNAL HYDRAULIC VALVE SS316 BETTS #CH48955SST WITH SHEAR SECTION ON SPOOL PIPE

1 HYDRAULIC HAND PUMP BETTS # HP46982SL LOCATED ON DRIVER'S SIDE REAR FRAME C/W FUSIBLE/FRANGIBLE PLUG ON DRIVER'S SIDE FRONT FENDER AND FUSIBLE PLUG AT THE EMERGENCY VALVE

1 3" QRB HYDROLET VALVE BETTS #QR713SST SEALS : YES

23 OUTLET FITTINGS 1 3" STAINLESS STEEL MALE CAMLOCK WITH DUST CAP AND KEEPER WIRE SEALS : YES

TOP OF THE TANK

43 MANHOLE BOX 1 DOT SPLASHBOX WITH FLOOR AND ROLLOVER PROTECTION 1.5" DRAIN HOSES LOCATED EACH SIDE

44 VENTING 1 DOT-407 PRESSURE/VACUUM VENT 3" NPT FORT VALE #R407/14204 MAWP 35 PSIG, TEST 52.5 PSIG, WITH TEFLON O-RING SEAT INSTALLED ON 3" NPT NIPPLE IN SPILLBOX FLOOR TO REAR OF MANHOLE OFFSET TO CURBSIDE C/W S.S. BALL VALVE, PRESSURE GAUGE (0-60 PSIG) AND S.S. CHICAGO COUPLER (3/4" CONNECTION) SEALS : YES

45 VACUUM BREAKER N/A

46 AIR UNLOAD LINE 1 S.S. 1,25" AIR LINE FROM C/S FRT WITH BALL VALVE, GAUGE AND COUPLER TO DAM WITH A JUMPER HOSE AND AIR FILTER WILKERSON.

47 CATWALK 1 11.75" WIDE ALUMINIUM DIAMOND GRIP AT 2 O'CLOCK FROM FRONT TO REAR CLEAN OUTS ON CURBSIDE

50 LADDER 1 STD S.S. LADDER FLUSH MOUNTED TO CATWALK WITH DOUBLE RISERS ADD TWO GRAB HANDLES AT TOP OF CATWALK ON OUTER EDGE BOLTED ON SUPPORTS LOCATED NEAR CENTER ON CURBSIDE

51 SAFETY RAILING N/A

SUSPENSION

52 SUSPENSION BOGIE 3/16" STAINLESS STEEL, 13" HEIGHT

53 TYPE OF SUSPENSION 2 INTRAAX AANT23K, 23000LBS, 15" R.H. SPREAD: 49"

APPROVED: \_\_\_\_\_
DATE: \_\_\_\_\_